


Kołnierze luźne, kwasoodporne PN 10 (DIN 2642)

Wykonane zgodnie z DIN2642. Dostępne w gatunkach: 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu



DN	Rura	Kołnierz				Śruby			waga
		Dz	Dw	g	Dp	liczba	gwint	Do	
10	14.0	90	16	14	60	4	M 12	14	0.60
	17.2		19						
	18.0		20						
15	20.0	95	22	14	65	4	M 12	14	0.69
	21.3		24						
	23.0		26						
20	25.0	105	28	14	75	4	M 12	14	0.81
	26.9		30						
	28.0		31						
25	30.0	115	33	16	85	4	M 12	14	1.11
	33.7		36						
	35.0		40						
32	38.0	140	42	16	100	4	M 16	18	1.64
	42.4		46						
	43.0		48						
40	44.5	150	50	16	110	4	M 16	18	1.86
	48.3		54						
	54.0		59						
50	57.0	165	62	16	125	4	M 16	18	2.20
	60.3		65						
	69.0		73						
65	76.1	185	81	16	145	4	M 16	18	2.62
	84.0		90						
	88.9		94						
80	104.0	200	109	18	160	8	M 16	18	3.32
	108.0		113						
	114.3		119						
100	129.0	220	134	18	180	8	M 16	18	3.67
	133.0		138						
	139.7		145						
125	154.0	250	160	18	210	8	M 16	18	4.54
	159.0		164						
	168.3		173						
150	204.0	285	210	18	240	8	M 20	22	5.60
	219.1		225						
	254.0		260						
200	267.0	340	273	20	295	8	M 20	22	7.46
	273.0		279						
	306.0		311						
250	318.0	395	323	22	350	12	M 20	22	10.3
	323.9		329						
	355.0		361						
300	355.6	445	362	26	400	12	M 20	22	14.0
	368.0		374						
	405.0		411						
350	406.4	505	413	28	460	16	M 20	22	18.5
	419.0		426						
	456.0		465						
400	457.2	565	465	32	515	16	M 24	26	25.0
	459.0		465						
	506.0		515						
450	508.0	615	517	38	565	20	M 24	26	32.6
	521.0		531						
	506.0		515						
500	508.0	670	517	38	620	20	M 24	26	37.0
	521.0		531						
	600		618						
600	610.0	780	618	44	725	20	M 27	30	56.3
	700		721						
	711.0		721						
700	711.0	895	721	50	840	24	M 27	30	80.4
	800		824						
	813.0		824						
800	813.0	1015	824	56	950	24	M 30	33	113.2