

Kołnierze luźne przetłaczane PN 10

Wykonane zgodnie z DIN2642. Alternatywa dla kołnierza luźnego nierdzewnego.
Taka sama wytrzymałość przy niższej wadze i cenie.

DN	Ø zew.	e	d	b	n	o	c	waga kg	0H18N9	00H17N14M2
15	95	3	24	9.5	4	13.5	65	0.20	•	•
20	105	3	30	12.5	4	13.5	75	0.24	•	•
25	115	3	36	14.5	4	13.5	85	0.26	•	•
32	140	3	46	16.5	4	17.5	100	0.45	•	•
40	150	4	54	17.5	4	17.5	110	0.65	•	•
50	165	4	65	19.5	4	17.5	125	0.80	•	•
65	185	4	81	21.0	4	17.5	145	0.95	•	•
80	200	5	94	21.0	8	17.5	160	1.38	•	•
100	220	6	119	23.0	8	17.5	180	1.60	•	•
125	250	6	145	24.0	8	17.5	210	2.00	•	•
150	285	7	174	26.0	8	21.5	240	2.60	•	•
200	340	8	225	29.0	8	21.5	295	3.20	•	•
250	395	8	280	32.0	12	21.5	350	4.40	•	•
300	445	8	330	35.0	12	21.5	400	5.80	•	•

