


Kołnierz luźny typu „lap joint”

Ciśnienie pracy 150Lbs. Stosować w połączeniu z kołnierzem wywijającym typu „stube end”.

Dostępny w gatunkach 1.4541, 1.4571, 1.4404.

Na zamówienie dostępne w klasach 300, 400, 600, 900, 1500, 2500Lbs,



Wymiar	cale / mm	Dz	Dp	Dw	H	r	M	g	I. Otworów	Do	Waga
1/2"	cale	3.50	2.38	0.90	0.62	0.12	1.19	0.44	4	0.62	0.51
	mm	90	60.3	22.9	16	3	30.0	11.2			
3/4"	cale	3.88	2.75	1.11	0.62	0.12	1.50	0.50	4	0.62	0.64
	mm	100	69.9	28.2	16	3	38.0	12.7			
1"	cale	4.25	3.12	1.38	0.69	0.12	1.94	0.56	4	0.62	0.93
	mm	110	79.4	34.9	17	3	49.0	14.3			
1 1/4"	cale	4.62	3.50	1.72	0.81	0.19	2.31	0.62	4	0.62	1.16
	mm	115	88.9	43.7	21	5	59.0	15.9			
1 1/2"	cale	5.00	3.88	1.97	0.88	0.25	2.56	0.69	4	0.62	1.51
	mm	125	98.4	50.0	22	6	65.0	17.5			
2"	cale	6.00	4.75	2.46	1.00	0.31	3.06	0.75	4	0.75	2.38
	mm	150	120.7	62.5	25	8	78.0	19.1			
2 1/2"	cale	7.00	5.50	2.97	1.12	0.31	3.56	0.88	4	0.75	3.60
	mm	180	139.7	75.4	29	8	90.0	22.3			
3"	cale	7.50	6.00	3.60	1.19	0.38	4.25	0.94	4	0.75	4.04
	mm	190	152.4	91.4	30	10	108.0	23.9			
3 1/2"	cale	8.50	7.00	4.10	1.25	0.38	4.81	0.94	8	0.75	4.99
	mm	215	177.8	104.1	32	10	122.0	23.9			
4"	cale	9.00	7.50	4.60	1.31	0.44	5.31	0.94	8	0.75	5.96
	mm	230	190.5	116.8	33	11	135.0	23.9			
5"	cale	10.00	8.50	5.69	1.44	0.44	6.44	0.94	8	0.88	6.44
	mm	255	215.9	144.4	36	11	164.0	23.9			
6"	cale	11.00	9.50	6.75	1.56	0.50	7.56	1.00	8	0.88	7.59
	mm	280	241.3	171.4	40	13	192.0	25.4			
8"	cale	13.50	11.75	8.75	1.75	0.50	9.69	1.12	8	0.88	12.66
	mm	345	298.5	222.2	44	13	246.0	28.6			
10"	cale	16.00	14.25	10.92	1.94	0.50	12.00	1.19	12	1.00	16.78
	mm	405	362.0	277.4	49	13	305.0	30.2			
12"	cale	19.00	17.00	12.92	2.19	0.50	14.38	1.25	12	1.00	28.30
	mm	485	431.8	328.2	56	13	365.0	31.8			
14"	cale	21.00	18.75	14.18	3.12	0.50	15.75	1.38	12	1.12	41.50
	mm	535	476.3	360.2	79	13	400.0	35.0			
16"	cale	23.50	21.25	16.19	3.44	0.50	18.00	1.44	16	1.12	52.98
	mm	595	539.8	411.2	87	13	457.0	36.6			
18"	cale	25.00	22.75	18.20	3.81	0.50	19.88	1.56	16	1.25	59.00
	mm	635	577.9	462.3	97	13	505.0	39.7			
20"	cale	27.50	25.00	20.25	4.06	0.50	22.00	1.69	20	1.25	72.12
	mm	700	635.0	514.4	103	13	559.0	42.9			
24"	cale	32.00	29.50	24.25	4.38	0.50	26.12	1.88	20	1.38	99.02
	mm	815	749.3	616.0	111	13	663.0	47.7			