

# Kołnierze płaskie do spawania PN16

Dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H18N12M2, 0H22N24M4TCu

DN	Rura	Kołnierz				Śruby			waga
		Dz	Dw	g	Dp	liczba	gwint	Do	
10	13.5	90	14.5	14	60	4	M 12	14	0.60
	17.2		17.7						
15	18.0	95	18.5	14	65	4	M 12	14	0.67
	20.0		20.5						
	21.3		22.5						
20	23.0	105	24.0	16	75	4	M 12	14	0.86
	25.0		26.0						
	26.9		27.6						
25	28.0	115	30.0	16	85	4	M 12	14	1.10
	30.0		31.0						
	33.7		34.4						
32	35.0	140	36.0	16	100	4	M 16	18	1.65
	38.0		39.0						
	42.4		43.1						
40	43.0	150	44.0	16	110	4	M 16	18	1.86
	44.5		45.5						
	48.3		49.0						
50	54.0	165	55.0	18	125	4	M 16	18	2.50
	57.0		58.1						
	60.3		61.1						
65	69.0	185	70.0	18	145	4	M 16	18	3.00
	76.1		77.1						
80	84.0	200	85.5	20	160	8	M 16	18	3.76
	88.9		90.3						
100	104.0	220	105.0	20	180	8	M 16	18	4.20
	108.0		109.6						
	114.3		115.6						
125	129.0	250	131.0	22	210	8	M 16	18	5.60
	133.0		134.8						
	139.7		141.6						
150	154.0	285	156.0	22	240	8	M 20	22	6.70
	159.0		161.1						
	168.3		170.5						
200	204.0	340	206.5	24	295	12	M 20	22	9.92
	219.1		221.5						
	254.0		257.5						
250	267.0	405	270.3	28	355	12	M 24	26	13.8
	273.0		276.5						
	306.0		308.5						
300	318.0	460	321.5	32	410	12	M 24	26	17.6
	323.9		327.5						
	355.0		358.5						
350	355.6	520	359.0	36	470	16	M 24	26	27.3
	368.0		371.5						
	405.0		409.5						
400	406.4	580	411.0	38	525	16	M 27	30	34.4
	419.0		423.5						
	500		508.0						
600	610.0	840	616.5	44	770	20	M 33	36	74.5
800	813.0	1025	820.0	60	950	24	M 36	39	126
1000	1016.0	1255	1023	80	1170	28	M 39	42	236
1200	1220	1485	1226	95	1390	32	M 45	48	368
1400	1420	1685	1425	110	1590	36	M 45	48	490
1600	1620	1930	1626	125	1820	40	M 52	56	735
2000	2020	2345	2026	150	2230	48	M 56	62	1040

