


Kołnierze szyjkowe



Kołnierze szyjkowe PN10 (DIN 2632)
dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10,
00H17N14M2, 0H22N24M4TCu

DN	Rura	Kołnierz						Śruby			masa
	d ₁	Dz	g	Dp	h	s	d ₃	liczba	gwint	Do	
Od DN10 do DN150 stosować PN16											
200	219,1	340	24	295	62	5,9	268	8	M 20	22	11,3
250	267,0	395	26	350	68	6,3	320	12	M 20	22	14,7
	273,0										
300	323,9	445	26	400	68	7,1	370	12	M 20	22	17,4
350	355,6	505	26	460	68	7,1	430	16	M 20	22	23,6
	368,0										21,6
400	406,4	565	26	515	72	7,1	482	16	M 24	26	28,6
	419,0										26,2
500	508,0	670	28	620	75	7,1	585	20	M 24	26	38,1
600	610,0	780	28	725	80	7,1	685	20	M 27	30	44,6
700	711,1	895	30	840	80	8,0	800	24	M 27	30	62,4
800	813,0	1015	32	950	90	8,0	905	24	M 30	33	84,1
900	914,1	1115	34	1050	95	10	1005	28	M 30	33	98,5
1000	1016	1230	34	1160	95	10	1110	28	M 33	36	115
1200	1220	1455	38	1380	115	11	1330	32	M 36	39	182
1400	1420	1675	42	1590	120	12	1535	36	M 39	42	248
1600	1620	1915	46	1820	130	14	1760	40	M 45	48	347
1800	1820	2115	50	2020	140	15	1960	44	M 45	48	430
2000	2020	2325	54	2230	150	16	2170	48	M 45	48	539
2200	2220	2550	58	2440	160	18	2370	52	M 52	56	658
2400	2420	2760	62	2650	170	20	2570	56	M 52	56	825
2600	2620	2960	66	2850	180	22	2780	60	M 52	56	979
2800	2820	3180	70	3070	190	22	3000	64	M 52	56	1156
3000	3020	3405	75	3290	200	24	3210	68	M 56	62	1402