

Kołnierze szyjkowe PN64 DIN2636

Kołnierze szyjkowe dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.
Standardowo powierzchnia uszczelniająca - Forma E.
Na zamówienie kołnierze do średnic metrycznych oraz kołnierze z nietypowymi grubościami szyjek

DN	Rura	Kołnierz						Śruby			waga
	d1	Dz	g	Dp	h	s	d3	liczba	gwint	Do	
10	13.5 17.2	100	20	70	45	1.8	40	4	M 12	14	1.09
15	20.0 21.3	105	20	75	45	2.0	45	4	M 12	14	1.19
25	30.0 33.7	140	24	100	58	2.6	65	4	M 16	18	2.66
40	44.5 48.3	170	26	125	62	2.9	88	4	M 20	22	4.09
50	57.0 60.3	180	26	135	62	2.9	102	4	M 20	22	4.55
65	76.1	205	26	160	68	3.2	122	8	M 20	22	5.73
80	88.9	215	28	170	72	3.6	138	8	M 20	22	6.69
100	108.0 114.3	250	30	200	78	4.0	162	8	M 24	26	9.66
125	133.0 139.7	295	34	240	88	4.5	188	8	M 27	30	15.1
150	159.0 168.3	345	36	280	95	5.6	218	8	M 30	33	21.9
200	219.1	415	42	345	110	7.1	285	12	M 33	36	34.9
250	267.0 273.0	470	46	400	125	8.8	345	12	M 33	36	49.6
300	323.9	530	52	460	140	11.0	410	16	M 33	36	68.7
350	355.6 368.0	600	56	525	150	12.5	465	16	M 36	39	94.6
400	406.4	670	60	585	160	14.2	435	16	M 39	42	124.0

