


# Kołnierze szyjkowe PN100 DIN2637

Kołnierze szyjkowe dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.

Standardowo powierzchnia uszczelniająca - Forma E.

Na zamówienie kołnierze do średnic metrycznych oraz kołnierze z nietypowymi grubościami szyjek



DN	Rura		Kołnierz					Śruby			waga
	d1	Dz	g	Dp	h	s	d3	liczba	gwint	Do	
10	13.5	100	20	70	45	1.8	40	4	M 12	14	1.09
	17.2										
15	20.0	105	20	75	45	2.0	45	4	M 12	14	1.19
	21.3										
25	30.0	140	24	100	58	2.6	68	4	M 16	18	2.66
	33.7										
40	44.5	170	26	125	62	2.9	88	4	M 20	22	4.09
	48.3										
50	57.0	195	28	145	68	3.2	102	4	M 24	26	5.98
	60.3										
65	76.1	220	30	170	76	3.6	122	8	M 24	26	7.91
80	88.9	230	32	180	78	4.0	138	8	M 24	26	8.95
100	108.0	265	36	210	90	5.0	162	8	M 27	30	13.7
	114.3										
125	133.0	315	40	250	105	6.3	188	8	M 30	33	22.7
	139.7										
150	159.0	355	44	290	115	7.1	218	12	M 30	33	30.2
	168.3										
200	219.1	430	52	360	130	10.0	285	12	M 33	36	52.8
250	267.0	505	60	430	157	12.5	345	12	M 36	39	81.4
	273.0										
300	323.9	585	68	500	170	14.2	410	16	M 39	42	122
350	355.6	655	74	560	189	16.0	465	16	M 45	48	165