


Kołnierze zaślepiające ANSI 150Lbs ASME


Kołnierze zaślepiające dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.



DN	Cal.	Kołnierz				Śruby			waga
		Dz	g	Dp	d3	liczba	gwint	Do	
15	1/2"	88.9	11.1	60.3	34.9	4	12.7	15.9	0.8
20	3/4"	98.4	12.7	69.8	42.9	4	12.7	15.9	0.9
25	1"	107.9	14.3	79.4	50.8	4	12.7	15.9	1.0
32	1 1/4"	114.5	15.9	88.9	63.5	4	12.7	15.9	1.3
40	1 1/2"	127.0	17.5	98.4	73.0	4	12.7	15.9	1.4
50	2"	152.4	19.0	120.6	92.1	4	15.9	19	1.8
65	2 1/2"	177.8	22.2	139.7	104.8	4	15.9	19	3.2
80	3"	190.5	23.8	152.4	127.0	4	15.9	19	4.1
	3 1/2"	215.9	23.8	177.8	139.7	8	15.9	19	5.9
100	4"	228.6	23.8	190.5	157.2	8	15.9	19	7.7
125	5"	254.0	23.8	215.6	185.7	8	19.0	22.2	9.1
150	6"	279.4	25.4	241.3	215.9	8	19.0	22.2	11.8
200	8"	342.9	28.6	298.4	269.9	8	19.0	22.2	20.4
250	10"	406.4	30.2	361.9	323.8	12	22.2	25.4	31.8
300	12"	482.6	31.7	431.8	381.0	12	22.2	25.4	50.0
350	14"	533.4	34.9	476.2	412.7	12	25.4	28.6	60.0
400	16"	596.9	36.5	539.7	469.9	16	25.4	28.6	77.0
450	18"	635.0	39.7	577.8	533.4	16	28.6	31.7	95.0
	20"	698.5	42.9	635.0	584.2	20	28.6	31.7	123
500	22"	749.3	56.0	692.1	641.2	20	31.7	34.9	151
600	24"	812.8	47.6	749.3	692.1	20	31.7	34.9	187

Kołnierze zaślepiające ANSI 300Lbs ASME B16.5

Kołnierze zaślepiające dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.



DN	Cal.	Kołnierz				Śruby			waga
		Dz	g	Dp	d3	liczba	gwint	Do	
15	1/2"	95.2	14.3	66.7	34.9	4	12.7	15.9	1.0
20	3/4"	117.5	15.9	82.5	42.9	4	15.9	19.0	1.4
25	1"	128.3	17.5	88.9	50.8	4	15.9	19.0	1.8
32	1 1/4"	133.3	19.0	98.4	63.5	4	15.9	19.0	2.7
40	1 1/2"	155.6	20.6	114.3	73.0	4	19.0	22.2	3.2
50	2"	165.1	22.2	127.0	92.1	8	15.9	19.0	3.6
65	2 1/2"	190.5	25.4	149.2	104.8	8	19.0	22.2	5.4
80	3"	209.5	28.6	168.3	127.0	8	19.0	22.2	7.3
	3 1/2"	228.6	30.2	184.1	139.7	8	19.0	22.2	9.5
100	4"	254.0	31.7	200.0	157.2	8	19.0	22.2	12.2
125	5"	279.4	34.9	234.9	185.7	8	19.0	22.2	15.9
150	6"	317.5	36.5	269.9	215.9	12	19.0	22.2	22.7
200	8"	381.0	44.3	330.2	269.9	12	22.2	25.4	37.0
250	10"	444.5	47.6	387.3	323.9	16	25.4	28.6	58.0
300	12"	520.7	50.8	450.8	381.0	16	28.6	31.7	84.0
350	14"	584.2	54.0	514.3	412.7	20	28.6	31.7	107
400	16"	647.7	57.1	571.5	469.9	20	31.7	34.9	139
450	18"	711.2	60.3	628.6	533.4	24	31.7	34.9	177
	20"	774.7	63.5	685.8	584.2	24	31.7	34.9	223
500	22"	838.2	66.7	742.9	641.2	24	38.1	41.3	270
600	24"	914.4	69.8	812.8	692.1	24	38.1	41.3	342

