


Kołnierze zaślepiające ANSI 600Lbs ASME B16.5

Kołnierze zaślepiające dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.

DN	Cal.	Kołnierz				Śruby			waga
		Dz	g	Dp	d3	liczba	gwint	Do	
15	1/2"	95.2	14.3	66.7	34.9	4	12.7	15.9	1.0
20	3/4"	117.5	15.9	82.5	42.9	4	15.9	19.0	1.4
25	1"	123.8	17.5	88.9	50.8	4	15.9	19.0	1.8
32	1 1/4"	133.3	20.6	98.4	63.5	4	15.9	19.0	2.7
40	1 1/2"	155.6	22.2	114.3	73.0	4	19.0	22.2	3.6
50	2"	165.1	25.4	127.0	92.1	8	15.9	19.0	4.5
65	2 1/2"	190.5	28.6	149.2	104.8	8	19.0	22.2	6.8
80	3"	209.5	31.7	168.3	127.0	8	19.0	22.2	9.1
	3 1/2"	228.6	34.9	184.1	139.7	8	22.2	25.4	13.2
100	4"	273.0	38.1	215.9	157.2	8	22.2	25.4	24.5
125	5"	330.2	44.4	266.7	185.7	8	25.4	28.6	30.9
150	6"	355.6	47.6	292.1	215.9	12	25.4	28.6	39.0
200	8"	419.1	55.6	349.1	269.9	12	28.6	31.7	63.0
250	10"	508.0	63.5	431.8	323.8	16	31.7	34.9	105
300	12"	558.8	66.7	488.9	381.0	20	31.7	34.9	134
350	14"	603.2	69.8	527.0	412.7	20	34.9	38.1	172
400	16"	685.8	76.2	603.2	469.9	20	38.1	41.3	239
450	18"	742.9	82.5	654.0	533.4	20	41.3	44.4	302
500	20"	812.8	88.9	723.9	584.2	24	41.3	44.4	388
	22"	869.9	95.2	777.9	641.2	24	44.4	47.6	437
600	24"	939.8	101.6	838.2	692.1	24	47.6	50.8	533



Kołnierze zaślepiające ANSI 900Lbs ASME B16.5

Kołnierze zaślepiające dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.

DN	Cal.	Kołnierz				Śruby			waga
		Dz	g	Dp	d3	liczba	gwint	Do	
15	1/2"	120.6	22.2	82.5	34.9	4	19.0	22.2	1.8
20	3/4"	130.2	25.4	88.9	42.9	4	19.0	22.2	2.7
25	1"	149.2	28.6	101.6	50.8	4	22.2	25.4	4.1
32	1 1/4"	158.7	28.6	111.1	63.5	4	22.2	25.4	4.5
40	1 1/2"	177.8	31.7	123.8	73.0	4	25.4	28.6	6.4
50	2"	215.9	38.1	165.1	92.1	8	22.2	25.4	11.3
65	2 1/2"	244.5	41.3	190.5	104.8	8	25.4	28.6	15.9
80	3"	241.3	38.1	190.5	127.0	8	22.2	25.4	14.5
100	4"	292.1	44.4	234.9	157.2	8	28.6	31.7	24.5
125	5"	349.2	50.8	279.4	185.7	8	31.7	34.9	39.0
150	6"	381.0	55.6	317.5	215.9	12	28.6	31.7	51.0
200	8"	469.9	63.5	393.7	269.9	12	34.9	38.1	89.0
250	10"	546.1	69.8	469.9	323.9	16	34.9	38.1	132
300	12"	609.6	79.4	533.4	381.0	20	34.9	38.1	188
350	14"	641.2	85.7	558.8	412.7	20	38.1	41.3	224
400	16"	704.8	88.9	615.9	469.9	20	41.3	44.4	281
450	18"	787.4	101.6	685.8	533.4	20	47.6	50.8	400
500	20"	857.2	107.9	749.3	584.2	20	50.8	54.0	503
600	24"	1041.4	139.7	901.7	692.1	20	63.5	66.7	953

