


Kołnierze zaślepiające ANSI 1500Lbs ASME B16.5


Kołnierze zaślepiające dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.



DN	Cal.	Kołnierz				Śruby			waga
		Dz	g	Dp	d3	liczba	gwint	Do	
15	1/2"	120.6	22.2	82.5	34.9	4	19.0	22.2	1.8
20	3/4"	130.2	25.4	88.9	42.9	4	19.0	22.2	2.7
25	1"	149.2	28.6	101.6	50.8	4	22.2	25.4	4.1
32	1 1/4"	158.7	28.6	111.1	63.5	4	22.2	25.4	4.5
40	1 1/2"	177.8	31.7	123.8	73.0	4	25.4	28.6	6.4
50	2"	215.9	38.1	165.1	92.1	8	22.2	25.4	11.3
65	2 1/2"	244.5	41.3	190.5	104.8	8	25.4	28.6	15.9
80	3"	266.7	47.6	203.2	127.0	8	28.6	31.7	21.8
100	4"	211.1	54.0	241.3	157.2	8	31.7	34.9	33.0
125	5"	274.6	73.0	292.1	185.7	8	38.1	41.3	64.0
150	6"	393.7	82.5	317.5	215.9	12	34.9	38.1	72.0
200	8"	482.6	92.1	393.7	269.9	12	41.3	44.4	137
250	10"	584.2	107.9	482.6	323.8	12	47.6	50.8	230
300	12"	673.1	123.8	571.5	381.0	16	50.8	54.0	352
350	14"	749.3	133.3	635.0	412.7	16	57.1	60.3	461
400	16"	825.5	146.0	704.8	469.9	16	63.5	66.7	613
450	18"	814.4	161.9	774.7	533.4	16	69.8	73.0	835
500	20"	984.2	177.8	831.8	584.2	16	76.2	79.4	1062
600	24"	1168.4	203.2	990.6	692.1	16	88.9	92.1	1712

Kołnierze zaślepiające ANSI 2500Lbs ASME B16.5

Kołnierze zaślepiające dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.



DN	Cal.	Kołnierz				Śruby			waga
		Dz	g	Dp	d3	liczba	gwint	Do	
15	1/2"	133.3	30.2	88.9	34.9	4	19.0	22.2	3.2
20	3/4"	139.7	31.7	95.2	42.9	4	19.0	22.2	4.5
25	1"	158.7	34.9	107.9	50.8	4	22.2	25.4	5.4
32	1 1/4"	184.1	38.1	130.2	63.5	4	25.4	28.6	8.2
40	1 1/2"	203.2	44.4	146.0	73.0	4	28.6	31.7	11.3
50	2"	234.9	50.8	171.4	92.1	8	25.4	28.6	17.7
65	2 1/2"	266.7	57.1	196.8	104.8	8	28.6	31.7	25.4
80	3"	304.8	66.7	228.6	127.0	8	31.7	34.9	39.0
100	4"	355.6	76.2	273.0	157.2	8	38.1	41.3	60.0
125	5"	419.1	92.1	323.9	185.7	8	44.4	47.6	101
150	6"	482.6	107.9	368.3	216.9	8	50.8	54.0	157
200	8"	552.4	127.0	438.1	269.9	12	50.8	54.0	242
250	10"	673.1	165.1	539.7	323.9	12	63.5	66.7	465
300	12"	762.0	184.1	619.1	381	12	69.8	73.0	665

