

# Kołnierze szyjkowe ANSI 150Lbs ASME B16.5

Kołnierze szyjkowe dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.

DN	Cal.	Grubość	Rura		Kołnierz					Śruby			masa
			d1	Dz	g	Dp	h	s	d3	liczba	gwint	Do	
15	1/2"	10S	21.3	88.9	11.1	60.3	47.6	2.11	34.9	4	12.7	15.9	0.7
		40 S STD 80 S XS											
20	3/4"	10S	26.7	98.4	12.7	69.8	52.4	2.10	42.9	4	12.7	15.9	0.8
		40 S STD 80 S XS											
25	1"	10S	33.4	107.9	14.3	79.4	55.6	2.80	50.9	4	12.7	15.9	1.1
		40 S STD 80 S XS											
32	1 1/4"	10S	42.2	117.5	15.9	88.9	57.1	2.80	63.5	4	12.7	15.9	1.5
		40 S STD											
40	1 1/2"	10S	48.3	127.0	17.5	98.4	61.9	2.80	73.0	4	12.7	15.9	1.8
		40 S STD 80 S XS											
50	2"	10S	60.3	152.4	19.0	120.6	63.5	2.80	92.1	4	15.9	19.0	2.7
		40 S STD 80 S XS											
65	2 1/2"	10S	73.1	177.8	22.2	139.7	69.8	3.10	104.8	4	15.9	19.0	4.4
		40 S STD											
80	3"	10S	88.9	190.5	23.8	152.4	69.8	3.10	127.0	4	15.9	19.0	5.2
		40 S STD 80 S XS											
	3 1/2"	10S	101.6	215.9	23.8	177.8	71.4	3.10	139.7	4	15.9	19.0	5.4
		40 S STD 80 S XS											
100	4"	10S	114.3	229.6	23.8	190.5	76.2	3.10	157.2	8	15.9	19.0	7.5
		40 S STD 80 S XS											
125	5"	10S	141.3	254.0	23.8	215.9	88.9	3.40	185.7	8	15.9	22.2	9.2
		40 S STD											
150	6"	10S	168.3	279.4	25.4	241.3	88.9	3.40	215.9	8	19.0	22.2	11.0
		40 S STD 80 S XS											
200	8"	10S	219.1	342.9	28.6	298.5	101.6	3.80	269.9	8	19.0	22.2	18.4
		40 S STD											
250	10"	10S	273.0	406.4	30.0	361.9	101.6	4.20	323.9	12	19.0	25.4	25.5
		40 S STD 80 S XS											
300	12"	10S	323.9	482.0	31.7	431.8	114.3	4.60	381.0	12	22.2	25.4	37.0
		40 S STD											
350	14"	10S	355.6	533.4	34.9	476.2	127.0	4.80	412.8	12	22.2	28.5	51.0
		40 S STD											
400	16"	10S	406.4	596.9	36.5	539.7	127.0	4.80	469.9	16	25.4	28.5	61.5
		40 S STD											
450	18"	10S	457.1	635.0	39.7	577.8	139.7	4.80	533.4	16	25.4	32.0	71.5
		40 S STD											
500	20"	10S	508.0	698.5	42.9	635.0	144.5	5.50	584.2	20	28.6	32.0	85.0
		40 S STD											
550	22"	10S	558.8	749.3	46.0	692.1	149.2	6.40	641.2	20	31.7	35.0	102
		40 S STD											
600	24"	10S	609.6	812.8	47.6	749.3	152.4	6.35	692.2	20	28.6	35.0	119
		40 S STD											

