


Kołnierze szyjkowe ANSI



300 Lbs dostępne w gatunkach
00H18N10 00H17N14M2

DN	Cal	Gr.	Rura		Kołnierz					Śruby			masa
			D ₁	D _z	G	D _p	h	s	d ₃	liczba	gwint	Do	
15	1/2"	10 S	21,3	95,2	14,3	66,7	52,4	2,11	34,9	4	12,7	15,9	0,8
		40 S STD						2,77					
		80 S XS						3,73					
		160						4,75					
20	3/4"	10 S	26,7	117,5	15,9	82,5	57,1	2,11	42,9	4	15,9	19,1	1,4
		40 S STD						2,87					
		80 S XS						3,91					
		160						5,54					
25	1"	10 S	33,4	123,8	17,5	88,9	61,9	2,77	50,8	4	15,9	19,1	1,7
		40 S STD						3,38					
		80 S XS						4,55					
32	1 1/4"	10 S	42,2	133,4	19,0	98,4	65,1	3,56	63,5	4	15,9	19,1	2,2
40	1 1/2"	10 S	48,3	155,6	20,6	114,3	68,3	2,77	73,0	4	19,0	22,2	3,2
		40 S STD						3,68					
		80 S XS						5,08					
50	2"	10 S	60,3	165,1	22,2	127,0	69,8	2,77	92,1	8	19,0	19,1	3,6
		40 S						3,91					
		80 S XS						5,54					
65	2 1/2"	40 S STD	73,1	190,5	25,4	149,2	76,2	5,16	104,8	8	19,0	22,2	5,4
		80 S XS						7,01					
80	3"	10 S	88,9	209,5	28,6	168,3	79,4	3,05	127,0	8	19,0	22,2	7,3
		40 S STD						5,49					
		80 S XS						7,62					
	3 1/2"	10 S	101,6	228,6	30,2	184,1	81,0	3,05	139,7	8	19,0	22,2	8,2
		40 S STD						5,74					
		80 S XS						8,08					
100	4"	10 S	114,3	254,0	31,7	200,0	85,7	3,05	157,2	8	19,0	22,2	11,8
		40 S STD						6,02					
		80 S XS						8,56					
125	5"	40 S STD	141,3	279,4	34,9	235,0	98,4	6,55	185,7	8	19,0	22,2	16,0
		10 S						3,40					
		40 S STD						7,11					
150	6"	80 S XS	168,3	317,5	36,5	269,9	98,4	10,97	215,9	12	19,0	22,2	20,2
		10 S						3,76					
		40 S STD						8,18					
200	8"	80 S XS	219,1	381,0	41,3	330,2	111,1	12,7	269,9	12	22,2	25,4	31,2
		10 S						4,19					
		20 S						6,35					
250	10"	40 S STD	273,0	444,5	47,6	387,3	117,5	9,27	323,9	16	25,4	28,6	44,3
		80 S XS						12,7					
		10 S						4,57					
		40 S STD						9,53					
300	12"	80 S XS	323,9	520,7	50,8	450,8	130,2	12,7	381,0	16	28,6	31,7	63,5
		10 S						4,57					
		40 S STD						9,53					
350	14"	40 S STD	355,6	584,2	54,0	514,3	142,7	9,53	412,8	20	28,6	31,7	86,0
		80 S XS						12,7					
400	16"	40 S STD	406,4	647,7	57,1	571,5	146,1	9,53	469,9	20	31,7	34,9	112,0
		80 S XS						12,7					
450	18"	40 S STD	457,2	711,2	60,3	628,6	158,7	9,53	533,4	24	31,7	34,9	138,0
		80 S XS						12,7					
500	20"	40 S STD	508,0	774,7	63,5	685,8	161,9	9,53	584,2	24	31,7	34,9	172,0
		80 S XS						12,7					
550	22"	40 S STD	558,8	838,2	66,7	742,9	165,1	9,53	641,2	24	38,1	41,3	195,0
		80 S XS						12,7					
600	24"	40 S STD	609,6	914,4	69,8	812,8	168,3	9,53	692,1	24	38,1	41,3	247,0
		80 S XS						12,7					