


# Kołnierze szyjkowe ANSI 300Lbs ASME B16.5

Kołnierze szyjkowe dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.



DN	Cal.	Grubość	Rura		Kołnierz					Śruby			masa
			D1	Dz	g	Dp	h	s	d3	liczba	gwint	Do	
15	1/2"	10 S	21.3	95.2	14.3	66.7	52.4	2.11	34.9	4	12.7	15.9	0.8
		40 S STD						2.77					
		80 S XS						3.73					
20	3/4"	160	26.7	117.5	15.9	82.5	57.1	4.75	42.9	4	15.9	19.1	1.4
		10 S						2.11					
		40 S STD						2.87					
25	1"	80 S XS	33.4	123.8	17.5	88.9	61.9	3.38	50.8	4	15.9	19.1	1.7
		10 S						2.77					
		40 S STD						4.55					
32	1 1/4"	10 S	42.2	133.4	19.0	98.4	65.1	3.56	63.5	4	15.9	19.1	2.2
40	1 1/2"	10 S	48.3	155.6	20.6	114.3	68.3	2.77	73.0	4	19.0	22.2	3.2
		40 S STD						3.68					
		80 S XS						5.08					
50	2"	10 S	60.3	165.1	22.2	127.0	69.8	2.77	92.1	8	19.0	19.1	3.6
		40 S STD						3.91					
		80 S XS						5.54					
65	2 1/2"	40 S STD	73.1	190.5	25.4	149.2	76.2	5.16	104.8	8	19.0	22.2	5.4
		80 S XS						7.01					
		10 S						3.05					
80	3"	40 S STD	88.9	209.5	28.6	168.3	79.4	5.49	127.0	8	19.0	22.2	7.3
		80 S XS						7.62					
		10 S						3.05					
	3 1/2"	10 S	101.6	228.6	30.2	184.1	81.0	3.05	139.7	8	19.0	22.2	8.2
		40 S STD						5.74					
		80 S XS						8.08					
100	4"	10 S	114.3	254.0	31.7	200.0	85.7	3.05	157.2	8	19.0	22.2	11.8
		40 S STD						6.02					
		80 S XS						8.56					
125	5"	40 S STD	141.3	279.4	34.9	235.0	98.4	6.55	185.7	8	19.0	22.2	16.0
150	6"	10 S	168.3	317.5	36.5	269.9	98.4	3.40	215.9	12	19.0	22.2	20.2
		40 S STD						7.11					
		80 S XS						10.97					
200	8"	10 S	219.1	381.0	41.3	330.2	111.1	3.76	269.9	12	22.2	25.4	31.2
		40 S STD						8.18					
		80 S XS						12.70					
250	10"	10 S	273.0	444.5	47.6	387.3	117.5	4.19	323.9	16	25.4	28.6	44.3
		20 S						6.35					
		40 S STD						9.27					
300	12"	80 S XS	323.9	520.7	50.8	450.8	130.2	4.57	381.0	16	28.6	31.7	63.5
		10 S						12.70					
		40 S STD						12.70					
350	14"	40 S STD	355.6	584.2	54.0	514.3	142.7	9.53	412.8	20	28.6	31.7	86.0
400	16"	40 S STD	406.4	647.7	57.1	571.5	146.1	9.53	469.9	20	31.7	34.9	112
		80 S XS						12.70					
		10 S						12.70					
450	18"	40 S STD	457.2	711.2	60.3	628.6	158.7	9.53	533.4	24	31.7	34.9	138
		80 S XS						12.70					
		10 S						12.70					
500	20"	40 S STD	508.0	774.7	63.5	685.8	161.9	9.53	584.2	24	31.7	34.9	172
		80 S XS						12.70					
		10 S						12.70					
550	22"	40 S STD	558.8	838.2	66.7	742.9	165.1	9.53	641.2	24	38.1	41.3	195
		80 S XS						12.70					
		10 S						12.70					
600	24"	40 S STD	609.6	914.4	69.8	812.8	168.3	9.53	692.1	24	38.1	41.3	247
		80 S XS						12.70					
		10 S						12.70					

