

Kołnierze szyjkowe ANSI 600Lbs ASME B16.5

Kołnierze szyjkowe dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.

DN	Cal.	Grubość	Rura		Kołnierz						Śruby			masa
			D1	Dz	g	Dp	h	s	d3	liczba	gwint	Do		
15	1/2"	40 S 80 S	21.3	95.2	14.3	66.7	52.4	2.77 3.73	34.9	4	12.7	15.9	0.9	
20	3/4"	40 S 80 S	26.7	117.5	15.9	82.5	57.1	2.87 3.91	42.9	4	15.9	19.1	1.6	
25	1"	10 S 40 S 80 S XS	33.4	123.8	17.5	88.9	61.9	2.77 3.38 4.55	50.8	4	15.9	19.1	1.9	
32	1 1/4"	10 S	42.2	133.4	20.6	98.4	66.7	3.56	63.5	4	15.9	19.1	2.6	
40	1 1/2"	40 S 80 S XS	48.3	155.6	22.2	114.3	69.8	3.68 5.08	73.0	4	19.0	22.2	3.6	
50	2"	10 S 40 S 80 S XS	60.3	165.1	25.4	127.0	73.0	2.77 3.91 5.54	92.1	8	15.9	19.1	4.7	
65	2 1/2"	10 S 40 S STD 80 S XS	73.1	190.5	28.6	149.2	79.4	3.05 5.49 7.62	104.8	8	19.0	22.2	8.2	
80	3"	40 S 80 S XS	88.9	209.5	31.7	168.3	82.5	5.49 7.62	127.0	8	19.0	22.2	8.7	
100	3 1/2"	40 S 80 S XS	101.6	228.6	34.9	184.1	85.7	5.74 8.08	139.7	8	22.2	22.2	11.8	
	4"	40 S 80 S XS	114.3	273.0	38.1	215.9	101.6	6.02 8.56	157.2	8	22.2	25.4	18.4	
125	5"	40 S 80 S XS	141.2	330.2	44.4	266.7	114.3	6.55 9.52	185.7	8	25.4	28.6	30.9	
150	6"	40 S 80 S XS	168.3	355.6	47.6	292.1	117.5	7.11 10.97	215.9	12	25.4	28.6	37.0	
200	8"	40 S 80 S XS	219.1	419.1	55.6	349.2	133.3	8.18 12.70	269.9	12	28.6	31.7	53.0	
250	10"	40 S 80 S XS	273.0	508.0	63.5	431.8	152.4	9.27 12.70	323.8	16	31.7	34.9	86.0	
300	12"	40 S 80 S XS	323.9	558.8	66.7	488.9	155.6	9.52 14.70	381.0	20	31.7	34.9	103	
350	14"	nieokreślone	355.6	603.2	69.8	527.0	165.1	nieokreślone	412.7	20	34.9	38.1	158	
400	16"		406.4	685.8	76.2	603.2	177.8		469.9	20	38.1	41.3	218	
450	18"		457.2	742.9	82.5	654.0	184.1		533.4	20	41.3	44.4	252	
500	20"		508.0	812.8	88.9	723.9	190.5		584.2	24	41.3	44.4	313	
550	22"		558.8	869.9	95.2	777.9	196.8		641.2	24	44.4	47.6	327	
600	24"		609.6	939.8	101.6	838.2	203.2		692.1	24	47.6	50.8	376	

