

# Kołnierze szyjkowe ANSI 2500Lbs ASME B16.5

Kołnierze szyjkowe dostępne w gatunkach 1H18N9T, H17N13M2T, 00H18N10, 00H17N14M2, 0H22N24M4TCu.

DN	Cal	Rura		Kołnierz				Śruby				waga
		D1	Dz	g	Dp	h	s	d3	liczba	gwint	Do	
15	1/2"	21.3	133.3	30.2	88.9	73.0	nieokreślone	34.9	4	19.0	22.2	3.6
20	3/4"	26.7	139.7	31.7	95.2	79.4		42.9	4	19.0	22.2	4.1
25	1"	33.4	158.7	34.9	107.9	88.9		50.8	4	22.2	25.4	5.9
32	1 1/4"	42.2	184.1	38.1	130.2	95.2		63.5	4	25.4	28.6	9.1
40	1 1/2"	48.3	203.2	44.4	146.0	111.1		73.0	4	28.6	31.7	12.7
50	2"	60.3	234.9	50.8	171.4	127.0		92.1	8	25.4	28.6	19.1
65	2 1/2"	73.1	266.7	67.1	196.8	142.9		104.8	8	28.6	31.7	23.6
80	3"	88.9	304.8	66.7	228.6	168.3		127.0	8	31.7	34.9	43.0
100	4"	114.3	355.6	76.2	273.0	190.5		157.2	8	38.1	41.3	66.0
125	5"	141.2	419.1	92.1	323.9	228.6		185.7	8	44.4	47.6	111
150	6"	168.3	482.6	107.9	368.3	273.0		215.9	8	50.8	54.0	172
200	8"	219.1	552.4	127.0	438.1	317.5		269.9	12	50.8	54.0	262
250	10"	273.0	673.1	165.1	539.7	419.1		323.9	12	63.5	66.7	485
300	12"	323.9	762.0	184.1	619.1	463.5		381.0	12	69.8	73.0	730

