

# Blachy gorąco i zimnowalcowane



## rozkrój 1250x2500

Grubość	Waga arkusza	0H18N9 (1.4301)	00H18N10 (1.4306)	1H18N9T (1.4541)	H17N13M2T (1.4571)	00H17N14M2 (1.4404)	DUPLEX (1.4462)	0H22N24MTCu (1.4539)
0,5	12,5							
0,6	15,0							
0,7	17,5							
0,8	20,0							
1,0	25,0							
1,25	31,3							
1,5	37,5							
2,0	50,0							
2,5	62,5							
3,0	75,0							
4,0	100							
5,0	125							
6,0	150							
8,0	200							
10	250							
12	300							
15	375							
20	500							
25	625							
30	750							
35	875							

Powierzchnie szczotkowane, szlifowane i polerowane na lustro.

## rozkrój 1250x2500

Grubość	Waga arkusza	Szlifowana	Szczotkowana	Polerowana (BA)
0,6	15,0			
0,8	20,0			
1,0	25,0			
1,25	31,3			

## rozkrój 1250x2500

Grubość	Waga arkusza	Szlifowana	Szczotkowana	Polerowana (BA)
1,5	37,5			
2,0	50,0			
3,0	75,0			

Inne grubości oraz nietypowe formaty szlifowane są na zamówienie klienta w krótkich terminach dostaw. Na życzenie klienta blachy mogą być foliowane obustronnie.