


GR - V F-715
Gerade Reduzierschraubungen

Straight reducing couplings

Unions double de réduction



Reihe	PN	Ra ₁	Ra ₂	S ₁	S ₁	S ₂	L ₂	L ₂	Artikel	
L	250	8	6	17	14	14	40,0	11,0	GR-V 08/06 L	
		10	6	19	17	14	41,0	12,0	GR-V 10/06 L	
		10	8	19	17	17	41,0	12,0	GR-V 10/08 L	
		12	6	22	19	14	42,0	13,0	GR-V 12/06 L	
		12	8	22	19	17	42,0	13,0	GR-V 12/08 L	
		12	10	22	19	19	43,0	14,0	GR-V 12/10 L	
		15	6	27	24	14	43,5	14,0	GR-V 15/06 L	
		15	8	27	24	17	43,5	14,0	GR-V 15/08 L	
		15	10	27	24	19	45,0	15,0	GR-V 15/10 L	
		15	12	27	24	22	45,0	15,0	GR-V 15/12 L	
		160	18	8	32	27	17	45,0	14,5	GR-V 18/08 L
			18	10	32	27	19	46,0	15,5	GR-V 18/10 L
			18	12	32	27	22	46,0	15,5	GR-V 18/12 L
			18	15	32	27	27	48,0	16,5	GR-V 18/15 L
			22	12	36	32	22	48,0	17,5	GR-V 22/12 L
22	15		36	32	27	50,0	18,5	GR-V 22/15 L		
22	18		36	32	32	50,0	18,0	GR-V 22/18 L		
100	28	12	41	41	22	51,5	18,0	GR-V 28/12 L		
	28	15	41	41	27	52,0	19,5	GR-V 28/15 L		
	28	18	41	41	32	52,0	19,0	GR-V 28/18 L		
	28	22	41	41	36	54,0	21,0	GR-V 28/22 L		
	35	28	50	46	41	59,0	21,0	GR-V 35/28 L		
	42	28	60	55	41	61,5	22,5	GR-V 42/28 L		
	42	35	60	55	50	66,5	21,5	GR-V 42/35 L		

Reihe	PN	Ra ₁	Ra ₂	S ₁	S ₁	S ₂	L ₂	L ₂	Artikel	
S	630	8	6	19	17	17	47,0	18,0	GR-V 08/06 S	
		10	6	22	19	17	48,0	17,5	GR-V 10/06 S	
		10	8	22	19	19	48,0	17,5	GR-V 10/08 S	
		12	6	24	22	17	50,0	19,5	GR-V 12/06 S	
		12	8	24	22	19	50,0	19,5	GR-V 12/08 S	
		12	10	24	22	22	51,0	19,0	GR-V 12/10 S	
		14	10	27	24	22	54,0	20,5	GR-V 14/10 S	
		14	12	27	24	24	54,0	20,5	GR-V 14/12 S	
		400	16	10	30	27	22	54,5	20,0	GR-V 16/10 S
			16	12	30	27	24	54,0	20,0	GR-V 16/12 S
			16	14	30	27	27	57,0	21,5	GR-V 16/14 S
			20	10	36	32	22	60,0	22,0	GR-V 20/10 S
			20	12	36	32	24	60,0	22,0	GR-V 20/12 S
			20	14	36	32	27	63,0	23,0	GR-V 20/14 S
20	16		36	32	30	63,0	23,0	GR-V 20/16 S		
25	14		46	41	27	66,0	25,5	GR-V 25/14 S		
25	16		46	41	30	66,0	25,5	GR-V 25/16 S		
25	20		46	41	36	71,0	25,5	GR-V 25/20 S		
250	30	20	50	46	36	74,0	26,0	GR-V 30/20 S		
	30	25	50	46	46	77,0	26,5	GR-V 30/25 S		
	38	30	60	55	50	87,0	29,5	GR-V 38/30 S		
								GR-V		